

Product data sheet

LIGHT SNIPER SQUARE


03.4608/HI PAR 51/35W/GX10/10°25°40°

FLOS




High performance luminaires for embedded installation for halogen lamps with dichroic reflector, metal halide reflector or LED lamps. They offer a high comfort due to the back visual position of light source. Body of the luminaire made of two bodies of injected aluminium. Square front ring made of steel sheet 1mm thick with white matt finish. It incorporates shielded cones made in zamak injection in three sets: black, matt gold and chrome. Fixed, tilt and wall-washers versions. Spreading lens made in opal tempered glass in halogen fixed and tilt versions. In wall-washer versions a distribution lens made of borosilicate is incorporated. IP44

Light output 1




1 x Metal halide lamp

Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2100 lm	LOR	35%
Luminous efficacy	21 lm/W	Total flux	730 lm
CCT	3000 K	Total power	35 W
CRI	84		



1 x Metal halide lamp

Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2100 lm	LOR	25%
Luminous efficacy	15 lm/W	Total flux	530 lm
CCT	3000 K	Total power	35 W
CRI	84		



1 x Metal halide lamp

Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2100 lm	LOR	34%
Luminous efficacy	20 lm/W	Total flux	715 lm
CCT	3000 K	Total power	35 W
CRI	84		

Mounting mode

Ceiling recessed

Electric

System power: 35 W

Shape and measurements

Length: 3.94 in

Width: 3.94 in

Height: 5.91 in

Adjustability

Fixed

Protection

IP: 44