
Product data sheet

P-INF Q100L LED1300-927 LDO GD TL
60817971
ZUMTOBEL



LED ceiling-recessed luminaire without trim, "Stable White"; shielding angle 60°; lamp(s): LED1300-927; Colour rendering Ra > 90, colour temperature 2700 K (warm white); Chromaticity tolerance (initial MacAdam): 2; total power: 15 W; Luminaire luminous flux: 1443 lm, Luminaire efficacy: 96 lm/W; service life: 50000h at 95% luminous flux; includes control unit Slave luminaire for DALI control (DALI only); modular, high quality optical unit consisting of reflector and LED light chamber integrated in optimised thermal management of die-cast aluminium; smooth reflector gold colour coated, matt; reflector made of high-quality, UV-resistant polycarbonate; luminaire unit can be fitted quickly without tools using EASY-CLICK catch; IP44_IP20; luminaire wired with halogen-free leads; power connection: 5-pole connector terminal, loop-in/loop-out possible; mains voltage: 220-240V / 0/50/60Hz, for use with 220V DC central battery; tool-free quick installation using spring clips in ceilings of thickness 1-25mm; ceiling cutout: 100x100 mm, recessed depth: 106mm; weight: 0.56 kg; Note: UGR<19 for office applications compliant with EN12464 (depending on luminaire type); Note: Please order seating surround (planar surround) separately for installing the luminaire flush with the ceiling (see Accessories)

Light output 1



1 x LED

Nominal lamp power	15 W	LOR	85%
Lamp flux	1700 lm	Total flux	1443 lm
Luminous efficacy	96 lm/W	Total power	15 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.61 in
Width: 4.61 in
Height: 4.02 in
Weight: 0.6 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 15 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: II

Protection

IP: 20
Designation labels: CE, ENEC