



Product data sheet

SINUS RECESSED FRAME WHITE SAT. 1546MM
R33E154-9016E1940H3S
PLANLICHT




high output LED 4000K CRI 90 105,2W 12952lm DALI <https://katalog.planlicht.com/en-gb/fam-sinus/>

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1619 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	13.15 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1619 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	13.15 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1619 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	13.15 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1619 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	13.15 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1619 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	13.15 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1619 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	13.15 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1619 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	13.15 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1619 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	13.15 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 60.87 in

Width: 60.87 in

Height: 3.23 in

Adjustability

Fixed

Electric

System power: 105.2 W

Protection

IP: 40