Product data sheet

RECESSO BETA OPTI 4CELL 600 830
25789
FAGERHULT



IP 20

Installation Recessed mounting in suspended ceilings. Only for suspended ceilings with visible T-bars (15 or 25 mm). Connection Connection to snap-in terminal block 3-way or 5-way, 2,5 mm2. Can also be supplied with mains cable and earthed plug. Can also be equipped with the Wieland or Wago connection system. Design Body of white enamelled (RAL 9016) sheet steel. Openings along the entire body, outside the edge of the louvre for flow-through ventilation. Louvre Beta Opti – double parabolic side and cross reflectors in satin matt, metallized aluminium with ex-cellent reflective properties (>92 %), integrated into a single unit. Integrated in the unit, an acrylic (PMMA) diffuser film to create optimised light technology properties.The louvre in its standard design is equipped with protective foil over the light opening. The protective foil is easily removed after final cleaning/installation.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	31 W	CRI	80
Total flux	4333 lm	LOR	100%
Luminous efficacy	140 lm/W	Total power	31 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.50 in
Width: 23.50 in
Height: 2.80 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 31 W

Protection

IP: 20