


Product data sheet

LESS IS MORE 50
312342.004.1.76
RZB




IP
20

IK
03

Series: LESS IS MORE 50 Linear pendant luminaire for aesthetically sophisticated lighting. Housing made of extruded aluminium profile, powder-coated. End cap made of aluminium powder-coated. Canopy made of aluminium, powder-coated. Alea optical system: Reflector structure (ABS, aluminium vapour-plated, highly polished) with integrated diffuser made of non-yellowing plastic (PMMA) opal for glare-free light at the workstation (screen-compliant in accordance with DIN EN 12464-1). Suitable for pendant. 2-point steel cable suspension freely positionable and infinitely height-adjustable. Special lengths available on request. LED unit with integrated converter interchangeable and removable. Suitable for through-wiring. With sensors or as a safety luminaire on request. Colour: silver, matt (approx. RAL 9006) Length: 1127 mm Width: 57 mm Height: 75 mm Suspension length: 2000 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 Light source: LED Socket lamp2: Without base Colour temperature: 4000K System power: 46 W Rated luminous flux: 5050 lm Beam angle Down: 50° / 53° Luminous efficacy: 110 lm/W Control gear: Converter, dimmable, DALI Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	46 W	CRI	80
Total flux	5050 lm	LOR	62%
Luminous efficacy	110 lm/W	ULOR	18%
		Total power	46 W

Mounting mode

Pendant

Shape and measurements

Length: 2.24 in
Width: 44.37 in
Height: 2.95 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 46 W

Protection

IP: 20
IK: 03