



Product data sheet

TENTEC ACCENT RECESSED LUMINAIRE
TL2101503-33-40_23W
SCHMITZ | WILA



Tentec accent LED 4000 K Recessed Luminaire, Light distribution direct Downlight Product: TL2101503-33-40 Operating technology: independent driver required Light Technique CRI > 80 high chromaticity stability with 3SDCM (initial) beam angles $\alpha = 20^\circ, 40^\circ$ or 60° constant colour temperature 4000 K lifetime 50.000 h (L70) Aluminium reflector (Al99.98), high-polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised frame thickness of only 2 mm for homogeneous appearance in the ceiling frame colour white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 2-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 23 W Colour Rendering Index: 80 Colour Temperature: 4000 K Luminaire Luminous Flux: 2310 Lm System Efficiency: 89 Lm/W Half-peak Divergence $\alpha: 60^\circ$ Number Luminaires LZ: 0.05 Connector: screw connector, 2 x 1.5 mm² Reflector Size: Q08 Length: 102 mm Width: 102 mm Cut-out length: 95 mm Cut-out width: 95 mm Installation Depth RD: 105 mm Total Weight: 0.4 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record TL2101503-33-40_23W

Light output 1



1 x General service incandescent lamp

Nominal lamp power	26 W	LOR	100%
Lamp flux	2310 lm	Total flux	2310 lm
Luminous efficacy	89 lm/W	Total power	26 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.02 in

Width: 4.02 in

Height: 4.13 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 26 W

Appliance Class: II

Protection

IP: 20