Product data sheet

ALDO 3 FLOODLINGHTS AND COLUMN PROJECTORS ALD-30171-E-W40

LIGMAN










- Lamp LED - Colour 3000K and 4000K - Powder coated aluminium alloy housing - Adjustable stainless steel bracket - Two cable entries for through wiring - Bright and consistent distribution, with seamless treatment with continuous mounting - Constant voltage (CV) 24V - Remote driver is not included - DC24V input, DMX512 address with constant current control for RGBW products

Light output 1 (integrated)



Lamp type	LED	CCT	
Nominal lamp power	48 W	CRI	
Total flux	3175 lm	LOR	
Luminous efficacy	66 lm/W	Total power	

Mounting mode

Standing / Bollard, Ceiling mounted

Shape and measurements

Length: 39.37 in Width: 3.03 in Height: 28.35 in Weight: 1.85 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 48 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: III

Protection

IP: 65 IK: 08

Surface temperature: 40°C Designation labels: CE

4032 K 80 100% 48 W