


Product data sheet

ONDA2 P D1150 LED14000-830-60 LDE WH
42185003
ZUMTOBEL



Decorative diffuse LED Round luminaire with opal cover for pendant installation. Total power: 116.7 W, DALI controllable luminaire with LED converter; LED service life lasts 50000 h before luminous flux is reduced to 80% of the initial value. Chromaticity tolerance (initial MacAdam): 4. Luminaire luminous flux: 13870 lm, Luminaire efficacy: 119 lm/W. Colour rendering Ra > 80, colour temperature 3000 K to 6000K. aluminium housing in white enamelled finish. Plastic cover, opal in polymethylmethacrylate with frosted surface, fixed to frame. Includes electronic LED converter for DALI control. Luminaire wired with halogen-free leads. Dimensions: Ø1150 x 85 mm weight: 18 kg; Please order pendant set with corresponding cord length separately.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	116.7 W	CRI	80
Total flux	13870 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	116.7 W

Mounting mode

Pendant

Shape and measurements

Height: 3.35 in
Diameter: 45.28 in
Weight: 18 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 116.7 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 20
Designation labels: CE