

Product data sheet


RICHARD V
9.889.2056.00
LEIPZIGER LEUCHTEN



IP
55


Mounting height approx. 4.00 m - 5.00 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge -Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	100 W	LOR	59%
Lamp flux	10400 lm	ULOR	15%
Luminous efficacy	54 lm/W	Total flux	6153 lm
CCT	2000 K	Total power	115 W
CRI	25		



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	59%
Lamp flux	5600 lm	ULOR	15%
Luminous efficacy	40 lm/W	Total flux	3313 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Pole top mounted

Shape and measurements

Height: 24.21 in
Diameter: 9.84 in

Electric

System power: 83-115 W

Protection

IP: 55