


Product data sheet

ARIZONA 5 POST TOP LUMINAIRES
AR-21051-W40
LIGMAN



· Lamp COB · CRI Ra > 80 · MacAdam Ellipse 3 SDCM · Colour 3000K and 4000K · Life time L90B10 Ta 25° C 50,700 · Life time L80B10 Ta 50° C > 63,500 · Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance · Stainless steel fasteners in grade 316 · Durable silicone rubber gasket · High-efficiency optical reflector or PMMA lens · Clear, acrylic PMMA diffuser

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	3658 lm	LOR	100%
Luminous efficacy	93 lm/W	ULOR	7%
		Total power	39.3 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 150.98 in
Diameter: 8.86 in
Weight: 20 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 39.3 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C