

Product data sheet


MORITZ II (WALL FITTING)
9.542.3162.01
LEIPZIGER LEUCHTEN



IP
55

Mounting height of 4.50 to 6.00 m for medium or high light requirements - Luminaire made of cast aluminium, varnished - Superior lighting due to computer-optimised reflector system for sodium vapour high pressure discharge with clear glass tube bulb - Cover of single-pane safety glass, hinged - Cable protection hosing made of braided stainless steel - All electrical parts fitted -Available in any required RAL or DB colour without extra price - Special \varnothing 102 mm pole for 4.50 m mounting height, \varnothing 114 mm pole for 6.00 m mounting height, including pole mounting hot-dip galvanised and varnished are part of the delivery Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated


Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	41 lm/W
CCT	3400 K
CRI	54

LOR	82%
Total flux	5579 lm
Total power	137 W



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	37 lm/W
CCT	3400 K
CRI	54

LOR	82%
Total flux	3282 lm
Total power	89 W

Mounting mode

Wall mounted

Shape and measurements

Length: 21.26 in
Width: 6.89 in
Height: 21.26 in

Electric

System power: 89-137 W

Protection

IP: 55