


# Product data sheet

VERANDA 5 PILLAR LIGHT LUMINAIRES  
VR-70301-W40  
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, UV-stabilised polycarbonate lens - Integral control gear

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4032 K |
| Nominal lamp power | 15.7 W  | CRI         | 80     |
| Total flux         | 1214 lm | LOR         | 100%   |
| Luminous efficacy  | 77 lm/W | ULOR        | 17%    |
|                    |         | Total power | 15.7 W |

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 6.30 in  
Diameter: 6.30 in  
Weight: 1.7 kg

## Adjustability

Fixed

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 15.7 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 67  
IK: 08  
Surface temperature: 40°C