Product data sheet

CURVE DIRECT MATT WHITE 10W LED 3000K RA>80 5046611366

SG ARMATUREN









Round, attractive wall luminaire for horizontal/vertical installation and indoors/outdoors. Made of die-cast powder-coated aluminium. Glass diffuser. Can be mounted as a downlight or as an uplight, IP65, integrated LED, mounting back panel with two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK06. Light distribution Direct Light technic LED (not exchangeable) 10W 2700K or 3000K Ra>80 SDCM: 3 L70/B50 >50,000 hrs at Ta=25°C Control/Dimming Phase cut-off Protection Class I IP65 IK06 Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: Black (RAL 9004), Graphite (RAL 7024) or Matte white (RAL 9003) Optics: Tempered glass Mounting/Connection Surface Screwless terminal block

Light output 1 (integrated)



Lamp type
Nominal lamp power
Total flux
Luminous efficacy

LED	
10 W	
320 lm	
32 lm/W	

10 W

Mounting mode

Wall mounted

Shape and measurements

Length: 12.61 in Width: 4.07 in Height: 2.36 in

Adjustability

Fixed

Design

Color of housing: Black, Anthracite / graphite, White

Electric

System power: 10 W Appliance Class: I

Protection

IP: 65 IK: 06