


# Product data sheet

SMART LOTIS 160 IP55 LED GE 4000K FLOOD WHITE STRUC  
13014809  
MODULAR




Timeless Light Smart lotis is the best known fixture within the Smart family. The deeply recessed cone which holds the light source inspired the designers to create a very versatile spot to be combined with multiple accessories. This family's styling is based on our most popular designs. Concretely this means that the luminaires consist of a module (LED or halogen) which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or Smart surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...


## Light output 1




1 x LED			
Nominal lamp power	36.3 W	LOR	89%
Lamp flux	4427 lm	Total flux	3959 lm
Luminous efficacy	109 lm/W	Total power	36.3 W
CCT	4000 K		
CRI	90		




1 x LED			
Nominal lamp power	49.7 W	LOR	89%
Lamp flux	5725 lm	Total flux	5119 lm
Luminous efficacy	103 lm/W	Total power	49.7 W
CCT	4000 K		
CRI	90		




1 x LED			
Nominal lamp power	16 W	LOR	89%
Lamp flux	2265 lm	Total flux	2025 lm
Luminous efficacy	127 lm/W	Total power	16 W
CCT	4000 K		
CRI	90		



<b>1 x LED</b>			
Nominal lamp power	23.5 W	LOR	89%
Lamp flux	3084 lm	Total flux	2758 lm
Luminous efficacy	117 lm/W	Total power	23.5 W
CCT	4000 K		
CRI	90		



<b>1 x LED</b>			
Nominal lamp power	30.8 W	LOR	89%
Lamp flux	3828 lm	Total flux	3423 lm
Luminous efficacy	111 lm/W	Total power	30.8 W
CCT	4000 K		
CRI	90		



<b>1 x LED</b>			
Nominal lamp power	42 W	LOR	89%
Lamp flux	4972 lm	Total flux	4446 lm
Luminous efficacy	106 lm/W	Total power	42 W
CCT	4000 K		
CRI	90		

**Mounting mode**

Ceiling recessed

**Shape and measurements**

Length: 6.30 in  
Width: 6.30 in  
Height: 4.76 in  
Weight: 0.98 kg

**Adjustability**

Fixed

**Electric**

System power: 16-49.7 W  
Appliance Class: II

**Protection**

IP: 55