Product data sheet

CIRCULAR OUTWARD 2 RINGS (Ø1200 Ø900) CF4M-00V9AZDU05

LEDSC4








LedsC4 Circular Outward 2 Rings (ø1200 ø900) CF4M-00V9AZDU05V1 Pendant for indoor use. For sideways lighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 9 Product width or diameter (mm): 1177 Product height (mm): 6500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEAN WELL. Maximum power of light source: 117W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 7758. Real lm/W: 63. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 124. Power factor: 0.90. Dimmable equipment included: DALI-2.


Light output 1



| 1 x LED | |
|--------------------|---------|
| Nominal lamp power | 71.4 W |
| Lamp flux | 5210 lm |
| Luminous efficacy | 73 lm/W |
| CCT | 2700 K |
| CRI | 90 |

| LOR | 100% |
|-------------|---------|
| ULOR | 49% |
| Total flux | 5211 lm |
| Total power | 71.4 W |
| | |

Light output 2



| 1 x LED | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 52.6 W | LOR | 100% |
| Lamp flux | 2548 lm | ULOR | 49% |
| Luminous efficacy | 48 lm/W | Total flux | 2548 lm |
| CCT | 2700 K | Total power | 52.6 W |
| CRI | 90 | | |

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 47.24 in Width: 47.24 in Height: 1.18 in Electric

System power: 124 W Appliance Class: I

Protection

IP: 20

Adjustability

Fixed