

Product data sheet

LIGHT LINEAR VT 6 STREET AND AREA LUMINAIRES


VT-20024-T1-W40

LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket and clear toughened glass - Maximum wind load resistance is 120 km/h - Surge protection 10 kV

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 155 W | CRI | 80 |
| Total flux | 9378 lm | LOR | 100% |
| Luminous efficacy | 61 lm/W | Total power | 155 W |

Mounting mode

Pole integrated

Shape and measurements

Length: 3.54 in

Width: 5.91 in

Height: 35.24 in

Weight: 30.4 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 155 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 07

Surface temperature: 40°C