Product data sheet


TAREK R
911380.003.76
RZB



IP 20 IK 07

Series: Tarek Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium, rotates 356° horizontally and swivels 70° vertically, can be swivelled flush to the ceiling with magnetic lock. Reflector: faceted aluminium with anti-reflective safety glass, included, can be changed without tools, passive cooling. LED included together with connected converter in separate gearbox. Available Colours: deep black, matt (RAL 9005) Type of Installation: Recessed ceiling mounting Dimensions: D 180, H 3, HE 300 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 2700K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Luminaire flux LED: 4200lm System power: 45W Beam Angle: 43° Number of fittings B10A: 12 Number of fittings B16A: 20 Inrush current: 30A Unified Glare Ratio: 18,4 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	45 W	CRI	80
Total flux	4200 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	45 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 7.01 in
Diameter: 7.09 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: Black

Electric

System power: 45 W

Protection

IP: 20
IK: 07