

Product data sheet


ASYX 2 LED ASYMMETRIC FLOODLIGHT - SINGLE PENDANT
ASYX-X-L4-X-U-F-L27-1-UNV-X-X-X-STD
COOPER LIGHTING



IP
47

Nine lumen packages ranging from 3,000 - 34,000 lumens, Can be used indoors, outdoors (IP66) or in natatoriums, Warrantied for use in natatoriums (indoor pools) for 5 years, Standard 2700K, 3000K, 3500K all at +80CRI; 4000K minimum 70 CRI, Dual pendants, extension arms, & sloped ceiling mount available, Powder coated die-cast aluminum endcaps, Powder coated extruded aluminum housing, AccuLED optics optimize optical distributions and fixture spacing, WaveLinx wireless control option available, Aimable optics enable field adjustment (w/o impacting warranty / IP66)

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	215 W	CRI	80
Total flux	17343 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	100%
		Total power	215 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 6.00 in
Width: 12.00 in
Height: 0.39 in

Adjustability

Fixed

Electric

System power: 215 W

Protection

IP: 47