

Product data sheet

PITTSBURGH 2 FLOODLIGHTS, PROJECTORS AND COLUMN PROJECTORS


PIB-50012-T3-8030

LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Extruded aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Galvanized steel arm mounted - Thermal heat dissipation body - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency polycarbonate lens - Clear toughened glass - Integral control gear - Surge protection 10kV

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	56.7 W	CRI	80
Total flux	5550 lm	LOR	100%
Luminous efficacy	98 lm/W	ULOR	100%
		Total power	56.7 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	56.7 W	CRI	80
Total flux	5550 lm	LOR	100%
Luminous efficacy	98 lm/W	ULOR	100%
		Total power	56.7 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 16.93 in

Width: 35.43 in

Height: 20.59 in

Weight: 13 kg

Adjustability

Free

Electric

System power: 113.4 W

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 66

IK: 08

Surface temperature: 40°C