Product data sheet

KOCCA 1.1 W [3000K 8,5W 230VAC]
KA11115WH
L&L LUCE&LIGHT



IP 65 IK 06

Wall mounted for outdoor applications; surface mounted (wall); body in die-cast aluminium alloy EN AB 47100, screen in tempered glass; finishes: anthracite, white, cor-ten, grey; 1 power LED (4W), 1 power LED High Intensity (8,5W); 4W, 8,5W - 230Vac; built in power supply unit; connection box with 0,50 m cable H05RN-F 2x0,75 Ø6,3 mm; total delivered lumens: 102 lm (3000K, 4W), 323 lm (3000K, 8,5W); optics: asymmetrical 70°, asymmetrical 140°, asymmetrical 10°x70°, diffuse; LED colour: white - 2700K, 3000K, 4000K; ingress protection: IP65; impact resistance: IK06; operating temperature: -20°C+45°C; screen temperature: max 40°C (Ta 25°C); Glow Wire Test: 960°; photobiological safety: risk group 1 in accordance with EN62471:2006; appliance class: I; weight 1,80 kg; dimensions 100x100x120 mm

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	8.5 W	CRI	80
Total flux	206 lm	LOR	100%
Luminous efficacy	24 lm/W	Total power	8.5 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.94 in
Width: 4.72 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 8.5 W
Appliance Class: I

Protection

IP: 65
IK: 06