Product data sheet

OUTDOOR LIGHTING

V1-S1-00443-40Y32-6608027 TORNADO ROAD 80W 2700K ZHAGA


VARTON



IP 66 IK 09

LED street light luminaire. Tool-free access to the driver. Adjustable spigot. Cast aluminum housing, tempered protective glass. Application: roads and streets. Installation: pole and side-entry mounted (Ø48mm-60mm). AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Protection class: I Suitable for top end size, mm: 48...60 Mounting method: Side-entry Ingress protection (IP): IP66 Impact resistance: IK09 Power factor: 0,97 Color rendering index: 70-79 Nominal voltage, V: 220...230 https://www.varton.ru/products/ulichnoe-osveshchenie/tornado/tornado-road-dlya-dorogi/svetodiodnyy-svetilnik-varton-ulichnyy-tornado-road-kreplenie-na-konsol-80-vt-2700-k-ral9003-belyy-m/

Light output 1



1 x LED

Nominal lamp power	80 W	LOR	100%
Lamp flux	9600 lm	Total flux	9600 lm
Luminous efficacy	120 lm/W	Total power	80 W
CCT	2700 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 24.72 in
Width: 10.47 in
Height: 3.90 in

Adjustability

Fixed

Electric

System power: 80 W

Protection

IP: 66
IK: 09