

Product data sheet

FLAT BASIC
211400.002.1
RZB




IP
43

IK
02

Series: FLAT BASIC Decorative round surface-mounted luminaire. Base: plastic. Mouth blown 3-layer opal glass (Triplex glass) with satin finish. Diffuser fastening: spring system. Triplex glass produces particularly homogeneous, soft and glare free lighting. Suitable for ceiling mounting, wall (surface). Colour: pure white (RAL#160;9010) Diameter: 420#160;mm Height: 124#160;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 11#160;W Rated luminous flux: 1250#160;lm Luminous efficiency: 114#160;lm/W Control gear: AC Strom, dim.Ph.an-/abschnitt Protection class: I Type of protection: IP#160;43

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	11 W	CRI	80
Total flux	1250 lm	LOR	100%
Luminous efficacy	114 lm/W	ULOR	16%
		Total power	11 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.88 in
Diameter: 16.54 in

Adjustability

Fixed

Electric

System power: 11 W

Protection

IP: 43
IK: 02