
Product data sheet


LESS IS MORE 50
312320.004
RZB



IP 20 IK 03

Series: LESS IS MORE 50 Linear pendant luminaire for aesthetically sophisticated lighting. Housing made of extruded aluminium profile, powder-coated. End cap made of aluminium powder-coated. Canopy made of aluminium, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Suitable for pendant. 2-point steel cable suspension freely positionable and infinitely height-adjustable. Special lengths available on request. LED unit with integrated converter interchangeable and removable. Suitable for through-wiring. With sensors or as a safety luminaire on request. Colour: silver, matt (approx. RAL 9006) Length: 1687 mm Width: 57 mm Height: 75 mm Suspension length: 600-2000 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 Light source: LED Socket lamp2: Without base Colour temperature: 3000K System power: 59 W Rated luminous flux: 6900 lm Beam angle Down: 104° / 107° Luminous efficiency: 117 lm/W Control gear: Regulated power supply Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	59 W	CRI	80
Total flux	6900 lm	LOR	67%
Luminous efficacy	117 lm/W	ULOR	14%
		Total power	59 W

Mounting mode

Pendant

Shape and measurements

Length: 2.24 in
Width: 66.42 in
Height: 2.95 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 59 W

Protection

IP: 20
IK: 03