



Product data sheet

MAXI FLOODLIGHT 72LED 196W T4000 S60-OPT. AL
67510000400401-67510001400401
TELEVES



Televes Maxi Floodlight is a range of extremely efficient symmetric or asymmetric floodlights that can be used to illuminate large areas and sports. Designed around the latest LED technology. Model with 72 LEDs 4000K IRC>70 450mA. Maximum input power 196W. IP67. IK10. Class I. Light distribution Narrow 60°. System efficacy: Up to 150lm/W. Multi-array optics. Free adjustable bracket. Aerodynamic design. Body in extruded 6063 T5 aluminum. Excellent thermal management. Vent integrated to prevent moisture and balance atmosphere pressure. Standard finish in RAL9006. AVAILABLE DISTRIBUTIONS • PZ - Asymmetric • Wide Flood 90° • Narrow Flood 60° • Flood 30°

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	196 W	CRI	84
Total flux	29399 lm	LOR	100%
Luminous efficacy	150 lm/W	Total power	196 W

Mounting mode

Wall mounted, Pole integrated

Shape and measurements

Height: 0.16 in
Diameter: 3.46 in

Adjustability

Cardanic

Design

Material impression: Matt
Color of housing: White, Silver gray

Electric

System power: 196 W
Appliance Class: II

Protection

IP: 67
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -31...104°F