Product data sheet

OUTDOOR WALL R CG-S 40071354894

EATON EMERGENCY LIGHTING








• LED safety luminaire with high protection class (IP 65) for indoor and outdoor use • Robust construction from aluminium diecast and high impact resistant cover made of polycarbonate •Double terminal for through-wiring • High spacing by double optics technology and highly efficient HighPower LEDs • Minimum service requirement due to high service life of the LEDs (50,000 hours) • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation expenditures by STAR technology • Freely programmable mixed operation of the switching modes per luminaire in one circuit

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	5 W	CRI	70
Total flux	111 lm	LOR	100%
Luminous efficacy	22 lm/W	Total power	5 W

Mounting mode

Wall mounted

Shape and measurements

Length: 11.93 in Width: 7.24 in Height: 6.30 in

Adjustability

Fixed

Electric

System power: 5 W

Suitable for feed-through wiring

Appliance Class: I

Information regarding emergency functions

Emergency lighting only

Emergency power supply: Central battery feed-in

Emergency sign: N/A

Protection

IP: 65 IK: 10