

Product data sheet

RECHTECK WAND AUSLEGER
671065.002.1.04
RZB




IP
44

IK
03


Series: RECHTECK Rectangular wall extension luminaire in classic design. For escape route identification. Housing: aluminium, with plastic corner connectors. Display panels: plastic, opal, with motifs on one side/on both sides. Wall extension Electronic ballast included. Self-contained system with automatic self-test and feedback to the RZB monitoring system MULTIDIGIT. Please indicate legend number when placing your order! Colour: traffic white, matt (RAL 9016) Length: 362 mm Width: 125 mm Height: 192 mm Weight: 2.23 kg Operating mode: maintained power mode Viewing Distance: 32 m Duration time: 3 h Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 70 System power: 5.1 W Rated luminous flux: 110 lm Luminous flux, emergency: 55 lm System power, emergency: - Control gear: Regulated power supply Protection class: I Type of protection: IP 44

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.1 W	CRI	70
Total flux	110 lm	LOR	100%
Luminous efficacy	22 lm/W	ULOR	15%
		Total power	5.1 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.1 W	CRI	70
Total flux	55 lm	LOR	100%
Luminous efficacy	11 lm/W	ULOR	15%
		Total power	5.1 W

Mounting mode

Wall mounted

Shape and measurements

Length: 4.92 in
Width: 14.25 in
Height: 7.56 in

Electric

System power: 10.2 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Design

Color of housing: White

Protection

IP: 44

IK: 03