



Product data sheet

DUOMO SMALL SHADE WALL LUMINAIRES
DU-30123-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Two cable entries for through wiring - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Opal glass diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	20 W	CRI	80
Total flux	1375 lm	LOR	100%
Luminous efficacy	69 lm/W	ULOR	5%
		Total power	20 W

Mounting mode

Wall mounted

Shape and measurements

Height: 12.44 in
Diameter: 12.99 in
Weight: 3.7 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 20 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 55
IK: 04
Surface temperature: 40°C