


Product data sheet

LINA45-S 145S-5C1Z-20GEM3/830, S
145S-5C1Z-20GEM3/830
HALLA




145S-5C1Z-20GEM3/830, S Luminaire suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1122 x 47 x 69 mm Type of installation: Suspended Distribution: Direct-indirect clear plexi Optics type: Plastic louvre low UGR Protection class: I Voltage: 220-240V

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	22.8 W	CRI	80
Total flux	3270 lm	LOR	100%
Luminous efficacy	143 lm/W	Total power	22.8 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	250 lm	LOR	100%
Luminous efficacy	167 lm/W	Total power	1.5 W

Mounting mode

Pendant

Shape and measurements

Length: 1.85 in
Width: 44.17 in
Height: 2.72 in

Adjustability

Fixed

Electric

System power: 24.3 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20