
Product data sheet

MILEWIDE LED GEN2 LARGE BPP436 T25 1 XLED81-4S/827 DM32
BPP436
PHILIPS



MileWide LED gen2 - elegant, yet highly efficient and future-proof Together with Holscher Design, we have developed MileWide LED gen2, the successor to the highly popular MileWide family. Featuring a range of dedicated masts and brackets, the pure, clean design of MileWide LED gen2 integrates perfectly with today's and tomorrow's cityscape. Thanks to it's advanced LED engine, and use of application-tailored optics, MileWide LED gen2 delivers outstanding quality of light and light performance, enabling significant energy savings, yet still providing perfectly uniform light on the road. MileWide LED gen2 is also ready to be paired with lighting control and software applications because it is equipped with the Philips SR (System Ready) socket. This means it can be connected to advanced software applications, such as Interact City, at any time during its lifetime. Furthermore, each luminaire is uniquely identifiable, thanks to the Philips Service tag application. With a simple scan of a QR code, placed on the inside of the mast door, you gain instant access to the luminaire configuration, making maintenance and programming operations faster and easier, no matter what stage of the luminaire's lifetime.

Light output 1



1 x LED

Nominal lamp power	66 W	LOR	88%
Lamp flux	8200 lm	Total flux	7185 lm
Luminous efficacy	109 lm/W	Total power	66 W
CCT	2700 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 66 W

Shape and measurements

Length: 28.90 in
Width: 12.05 in
Height: 4.72 in