

Product data sheet


SINUS SUSP. 'Y' SILVER SAT. 1530MM
R33Y153-9006E1HCLX3S
PLANLICHT



IP
40


dynamic white LED 2700-6500K CRI 90 109,3W 11548lm DALI DT8 <https://katalog.planlicht.com/en-gb/fam-sinus/>

Light output 1 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	13.66 W	CRI	90
Total flux	1444 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13.66 W

Light output 2 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	13.66 W	CRI	90
Total flux	1444 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13.66 W

Light output 3 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	13.66 W	CRI	90
Total flux	1444 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13.66 W

Light output 4 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	13.66 W	CRI	90
Total flux	1444 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13.66 W

Light output 5 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	13.66 W	CRI	90
Total flux	1444 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13.66 W

Light output 6 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	13.66 W	CRI	90
Total flux	1444 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13.66 W

Light output 7 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	13.66 W	CRI	90
Total flux	1444 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13.66 W

Light output 8 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	13.66 W	CRI	90
Total flux	1444 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13.66 W

Mounting mode

Pendant

Shape and measurements

Length: 60.24 in

Width: 60.24 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 109.3 W

Color adjustable

Protection

IP: 40