


Product data sheet

OPT-P 115.830.1/DALI
OPT-P 115.830.1/DALI
LTS LICHT & LEUCHTEN



rectangular pendant luminaire with direct-indirect illumination for uniform and absolutely glare-free workplace lighting, can be combined with insert luminaire OPT-R... and free-standing luminaire OPT-S..., light component: direct 20% / indirect 80%, outstanding ease of maintenance, no UV and thermal emissions, innovative tube technology for glare-free illumination, advanced lens optics with a standard beam angle of 60°, aluminium housing with micropoint optics and rounded design, colour combinations top/bottom: black/white, white/white and RAL/RAL, Y-wire-rope suspension 2-fold with height adjustment (length: 1500 mm), transparent connecting cable (5-core, pre-fabricated), white ceiling box made fom ABS, ballast (LED converter) integrated (with DALI dimming) Lamp: LED Matrix | 830 | CRI 80 | 3000 K Lifetime: L90 B50 50.000 h / L80 B50 100.000 h / L80 B20 50.000 h EPREL light sources: 833899 Protection class: I Type of protection: IP20 Standards: CE,RoHS Dimensions (LxBxH): 1245 x 300 x 40 mm Weight: 6.420 kg Colour: black-white (article no. 665493), white-white (article no. 665495) Accessories: ZB-OR DONGLE Organic Response IR dongle kit ZB-OR GATEWAY Organic Response IoT Gateway Cascade Series ZB-OR-A SENSOR Organic Response sensor for surface mounting ZB-OR-P SENSOR/3000 Organic Response sensor for pendant mounting Manufacture: LTS Type: OPT-P 115.830.1/DALI

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	115.8 W	CRI	80
Total flux	13800 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	78%
		Total power	115.8 W

Mounting mode

Pendant

Shape and measurements

Length: 49.02 in
Width: 11.81 in
Height: 1.57 in

Electric

System power: 115.8 W
Appliance Class: I

Protection

IP: 20