


# Product data sheet

PRUNUS-F4-PA03-64LED-3000K-7560LM-46.7W  
LIGHTRONICS



PRUNUS F DESIGN WITH AN EYE FOR DETAIL The PRUNUS F is a round luminaire and available in four variants. This luminaire has a special appearance and is suitable for a large number of applications, such as residential areas, public squares, parks, business parks, district distributor roads, town and village centres, separate cycle paths and car parks. The PRUNUS F is available with a transparent, flat UV-stabilised polycarbonate light cover (F1/F2), a contoured light cover made from textured polycarbonate (F3) and a flat light cover made from transparent safety glass (F4).

### Light output 1 (integrated)



|                    |        |             |        |
|--------------------|--------|-------------|--------|
| Lamp type          | LED    | CCT         | 3000 K |
| Nominal lamp power | 46.7 W | CRI         | 70     |
| Total flux         | 104 lm | LOR         | 87%    |
| Luminous efficacy  | 2 lm/W | Total power | 46.7 W |

### Mounting mode

Pole top mounted, Ceiling mounted

### Shape and measurements

Height: 3.94 in  
Diameter: 19.69 in

### Adjustability

Fixed

### Design

Material impression: Aluminum  
Color of housing: Anthracite / graphite

### Electric

System power: 46.7 W

### Protection

IK: 10