

# Product data sheet


LEDDOWNLIGHTRC-HM R100-6W-5700-WH-GP  
140048188  
OPPLE



IP  
20

Housing:corrosionresistant cast aluminium; Reflector: High reflective material; Mounting ring: plastic, white; Installation: recessed;  
Dimensions:Φ110×62mm; Ceiling cutouts:Φ100mm; Power:5W; Lamp(s):LED 830; Colour temperature:5700K; Colour rendering:RA80; Total  
luminous flux of luminaire:520lm; Beam angle:75°; Light distribution:Lambert; Service life:30,000h at 70% luminous flux; Degree of  
protection:IP20(IP44 for exposed parts); Class of protection II; Mains voltage:220-240V/50-60Hz; Two fixing clips provided for tool-free  
installation in ceilings of thickness 5-25 mm

## Light output 1



1 x LED			
Nominal lamp power	6.4 W	LOR	100%
Lamp flux	498 lm	Total flux	498 lm
Luminous efficacy	78 lm/W	Total power	6.4 W
CCT	5700 K		
CRI	80		

## Mounting mode

Ceiling recessed

## Electric

System power: 6.4 W

## Shape and measurements

Length: 4.33 in

Width: 4.33 in

Height: 2.44 in

## Protection

IP: 20

## Adjustability

Fixed