

# Product data sheet


SMARTPARNEO  
SMARTPARNEO\_4000K\_10DEG (NATIVE)  
PROLIGHTS



IP  
65

The Smart ParNeo is an IP-rated, battery-powered spotlight that combines the key advantages of the iconic Smart BatPlus uplighter with a more flexible design, expanding the range of possible applications. Equipped with 7 × 10W RGB+WW LEDs and powered by SpektraOS for advanced color control and consistency, this fixture supports both battery operation with CRMX wireless control and wired operation through power supply and chassis-mount connectors, ensuring seamless integration without limitations in either wireless or wired setups. Smart ParNeo is compact and highly portable, featuring a round body with a flat base that makes it naturally suited for uplighting. It can also be easily converted into a focusable spotlight thanks to a quick-lock, self-standing sliding yoke, allowing use either as a ground-standing fixture or in suspended installations with cam-lock clamps. Additionally, the unit can be customized with a range of quick-mount colored covers, ideal for adapting the fixture to different event environments. A selection of light modifiers and accessories further enhances its functionality and versatility. The unit features built-in NFC for quick configuration and can be supplied with a fast-charging flight case for six units, making it perfectly suited for touring applications. The Smart ParNeo is the latest flexible and multipurpose addition to the iconic SmartBat series, setting a new benchmark in portable professional lighting.

## Light output 1 (integrated)



|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Lamp type          | LED     | CCT         | 4013 K  |
| Nominal lamp power | 32.56 W | CRI         | 92      |
| Total flux         | 2307 lm | LOR         | 100%    |
| Luminous efficacy  | 71 lm/W | Total power | 32.56 W |

## Mounting mode

Standing / Bollard, Floor mounted

## Electric

System power: 32.56 W

## Shape and measurements

Length: 4.17 in  
Width: 7.64 in  
Height: 7.28 in

## Protection

IP: 65

## Adjustability

Tiltable