

Product data sheet

NADJA II (WALL FITTING)
9.845.2056.05
LEIPZIGER LEUCHTEN




Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

| | | | |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 100 W | LOR | 77% |
| Lamp flux | 10400 lm | Total flux | 8025 lm |
| Luminous efficacy | 70 lm/W | Total power | 115 W |
| CCT | 2000 K | | |
| CRI | 25 | | |



1 x High pressure sodium vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 70 W | LOR | 77% |
| Lamp flux | 5600 lm | Total flux | 4321 lm |
| Luminous efficacy | 52 lm/W | Total power | 83 W |
| CCT | 2000 K | | |
| CRI | 25 | | |

Mounting mode

Wall mounted, Ceiling mounted

Shape and measurements

Height: 20.08 in
Diameter: 20.08 in

Design

Material impression: Matt

Electric

System power: 83-115 W
Ballast: ECG

Protection

IP: 55
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...95°F