
Product data sheet

NSIGHTWP 4/8 LED6400-840 MSP LST R WHMM
42928027
ZUMTOBEL



Compact LED Spotlight of 32 LED optics configured as 4/8 variant. Total power: 66.2 W, Luminaire with SwitchDim light control with LED converter; LED service life lasts 100000 h before luminous flux is reduced to 80% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 6490 lm, Luminaire efficacy: 98 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Luminaire or spotlight with MEDIUMSPOT distribution. Luminaire of aluminium, microtextured paint in white, matt. ambient temperature: -25°C to +50°C. Integrated IP68 plug/socket for plug & play connection. Installation to wall. Luminaire wired with halogen-free leads; degree of protection: IP66; class of protection: SC1, Dimensions: 369 x 292 x 118 mm weight: 9 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	66.2 W	CRI	80
Total flux	6490 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	66.2 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 14.53 in
Width: 11.50 in
Height: 4.65 in
Weight: 9 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 66.2 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 66
IK: 08
Designation labels: CE, ENEC