


Product data sheet

ATLANTIC LED O HB CG-S
40071354991
EATON EMERGENCY LIGHTING



• LED safety luminaire with high protection class (IP65) for indoor and outdoor use • Luminaire with limited surface temperatures for use in operating areas with fire hazard • Suitable for use in food processing industry acc. IFS • Robust construction from aluminium diecast and high impact resistant cover made of polycarbonate • Numerous knock-outs for cable entries and double terminal for through-wiring (outdoor wall only one cable entry) • Suitable for mounting heights up to 28 m by narrow beam optics and exceptionally efficient High Power LEDs • Spacing up to 24 m from luminaire to luminaire with optics for escape route illumination • Up to 15 m from luminaire to luminaire with optics for open area illumination • Minimum service requirement due to high service life of the LEDs (50,000 hours) • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation expenditures by STAR technology • Freely programmable mixed operation of the switching modes per luminaire in one circuit

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	5 W	CRI	70
Total flux	170 lm	LOR	100%
Luminous efficacy	34 lm/W	Total power	5 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.93 in

Width: 5.35 in

Height: 2.44 in

Adjustability

Fixed

Electric

System power: 5 W

Suitable for feed-through wiring

Appliance Class: I

Information regarding emergency functions

Emergency lighting only

Emergency power supply: Central battery feed-in

Emergency sign: N/A

Protection

IP: 65

IK: 10