


# Product data sheet

MODSU L35 E3  
MOD SURFACE/SUSPENDED UGR EMERGENCY  
DEXTRA




MOD Surface / Suspended UGR - 600x600, IP40, IK08 Surface mounted luminaire, white powder coated steel body, high transmission microprism diffuser. Options: E3 - Emergency control gear (333 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* H - High Frequency Dimming (Analogue 1-10v) RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence

### Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21.6 W	CRI	80
Total flux	2286 lm	LOR	100%
Luminous efficacy	106 lm/W	ULOR	4%
		Total power	21.6 W

### Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	333 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	4%
		Total power	3 W

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 23.62 in  
Width: 23.62 in  
Height: 4.02 in

### Adjustability

Fixed

### Electric

System power: 24.6 W  
Ballast: ECG

### Information regarding emergency functions

Supplementary emergency lighting  
Emergency sign: N/A

## Protection

IP: 20

IK: 08

Designation labels: CE