

Product data sheet


MORITZ II (WALL FITTING)
9.542.6032.01
LEIPZIGER LEUCHTEN



IP
55

Mounting height of 4.50 to 6.00 m for medium or high light requirements - Luminaire made of cast aluminium, varnished - Superior lighting due to computer-optimised reflector system for sodium vapour high pressure discharge with clear glass tube bulb - Cover of single-pane safety glass, hinged - Cable protection hosing made of braided stainless steel - All electrical parts fitted -Available in any required RAL or DB colour without extra price - Special $\varnothing$ 102 mm pole for 4.50 m mounting height, $\varnothing$ 114 mm pole for 6.00 m mounting height, including pole mounting hot-dip galvanised and varnished are part of the delivery Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	78%
Lamp flux	7000 lm	Total flux	5454 lm
Luminous efficacy	61 lm/W	Total power	89 W
CCT	3000 K		
CRI	90		

Mounting mode

Wall mounted

Electric

System power: 89 W

Shape and measurements

Length: 21.26 in
Width: 6.89 in
Height: 21.26 in

Protection

IP: 55