


Product data sheet

6012/1124-4951-1100-11
226394
STAHL



Linear luminaire for fluorescent lamps sheet steel Enclosure material: Sheet-steel Lens material: Safety glass Enclosure colour: white, RAL 9016 Number of lamps: 4 Lamp wattage: 36 W Dimensions (L x W x H): 1.340 x 480 x 87 mm Rated operational voltage AC: 220,00 - 240,00 V Rated operational voltage DC: 220,00 - 240,00 V Application range (Zone): 1 , 2 , 21 , 22 Gas explosion protection: II 2 G Ex de IIC T4 Gb Dust explosion protection: II 2 D Ex tb IIIC Db T80 °C Min. ambient temperature: -35 °C Max. ambient temperature: +60 °C Type of protection (IP): IP65 Through wiring: with 5 conductors 2.5 mm² Drilled hole: 3 x M25 Cable entry: 2 x M25 Ø 7 – 17 mm Material of cable entry: polyamide black Plug: 1 x M25 x 1,5 Material stopping plug: polyamide black For further information, see: www.r-stahl.com Web code 6012B

Light output 1



4 x Fluorescent lamp tubular T5

Nominal lamp power	36 W	Socket	G13
Lamp flux	3350 lm	LOR	68%
Luminous efficacy	64 lm/W	Total flux	9160 lm
CCT	4000 K	Total power	144 W
CRI	85		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 52.76 in
Width: 18.90 in
Height: 4.84 in

Adjustability

Fixed, Tiltable, Free

Design

Color of housing: White

Electric

System power: 144 W
Appliance Class: I

Protection

IP: 65
IK: 08