


Product data sheet

ALU-STAR MIDI
721810.0031
RZB




IP
65

IK
07

Series: ALU-STAR midi High efficient LED outdoor floodlight. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. Thermally decoupled driver compartment, integral driver. With membrane valve as a standard to avoid condensed water. Rotation-symmetric reflector made of reflex-boosted MIRO-SILVER. Cover clear single-pane toughened glass. Wide flood. COB LED with socket for easy replacement. Stainless steel fixing clips with compensation for drill hole deviations. Rotation angle can be adjusted and locked in 3,6°/degree steps, tilt angle in 5°/degree steps with angular scale. Piano-key terminal up to 2x 5x 2,5 mm², max cable Ø 13mm, comes with second cable gland for loop through. Colour: anthracite metallic (DB703) Length: 255mm Width: 240mm Height: 255mm Lamp: LED System power: 56W Rated luminous flux: 6350lm Luminous efficiency: 113lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP65

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	56 W	CRI	80
Total flux	6350 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	56 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 9.45 in

Width: 10.04 in

Height: 10.04 in

Adjustability

Tiltable

Electric

System power: 56 W

Protection

IP: 65

IK: 07