Product data sheet


GALLERYWASHDATVW_WHITE
GALLERYWASHDATVW_FULL_SMOOTH FILTER
PROLIGHTS



IP 66 IK 08

Gallery WashDAT is a compact and efficient LED wallwash luminaire, purpose-designed for precise, uniform illumination of walls, exhibits, and shelving in galleries, events, and venues. Its advanced optical system combines a custom linear LED source with an asymmetrical reflector, significantly reducing the required number of fixtures by enabling greater spacing without compromising visual comfort or uniformity. The Gallery WashDAT VW variant includes a 60W variable white LED source, providing adjustable color temperatures ranging smoothly from warm 2'700K to cool 5'600K. This model excels in applications requiring precise white-light control to enhance visual clarity and ambiance. Control flexibility is assured through integrated RDM, DMX, and intuitive local dimming. Optional wireless control modules (LumenRadio CRMX) can be specified to simplify installation and enhance operational convenience. With its stylish cubic form factor, Gallery WashDAT integrates seamlessly into both contemporary interiors and historic venues. The integrated power supply and driver facilitate straightforward installation, further supported by an extensive range of accessories, including track adapters, adjustable yokes, ceiling mounting kits, and optical modifiers such as barn doors, holographic filters, and snoots. Main features: 60W Variable White linear LED engine offers dynamic color mixing and precision tunable white lighting Custom asymmetrical reflector ensures superbly uniform wall illumination, minimizing fixture count and installation complexity Supports RDM, DMX, local knob dimming, and optional wireless protocols (CRMX) for flexible and intuitive operation Integrated power supply with extensive mounting accessories and optical modifiers enables quick installation and precise customization for any venue

Light output 1



1 x LED

Nominal lamp power	53.4 W	LOR	100%
Lamp flux	3689 lm	Total flux	3696 lm
Luminous efficacy	69 lm/W	Total power	53.4 W
CCT	4144 K		
CRI	95		

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 39.37 in
Width: 39.37 in
Height: 39.37 in

Adjustability

Rotatable, Tiltable, Free

Electric

System power: 53.4 W
Controller: DMX
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 70°C
Designation labels: CE