


Product data sheet

SE7EN BOLLARD
7170-N-3-921-XX
UNILAMP



Description Angular designed bollard installed with OSRAM LED and manufactured with corrosion resistant extruded aluminium. SE7EN is architectural when off but simply better on. No visible screws, no light spill over the horizontal, pre wired cable with IP68 connections and IP66 lamp compartment SE7EN ticks all the construction boxes. It can be installed in walkways, parks, commercial areas and open spaces. It provides directional illumination for any architectural environ as well as being an eye-catching object. SPEC • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • Weather proof TPE grommet. • Bollard pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	5.2 W	LOR	53%
Lamp flux	750 lm	Total flux	399 lm
Luminous efficacy	144 lm/W	Total power	7 W
CCT	3000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 7.02 in
Width: 11.40 in
Height: 30.94 in

Adjustability

Fixed

Electric

System power: 7 W
Appliance Class: II

Protection

IP: 66
IK: 08