


Product data sheet

HERNING POLE MIDI GREY 1140LM 4000K RA>80 TRAILING EDGE DIMMING
7021986239812 + 7021986239737
SG ARMATUREN



With its combination of modern elegance and classic design, Hering Pole is ideal for illuminating gardens, walkways or other outdoor areas. Its glare-free light creates a pleasant atmosphere while providing optimal illumination. The bollard is compatible with both the Hering Mini and Midi pole heads, allowing you to create a cohesive look in your outdoor space with bollards, poles, and wall lights in the same timeless design. The pole and pole heads are sold separately. Hering Pole is made from durable, powder-coated steel, and the luminaire has a tempered glass front. Behind the glass, you'll find practical switches that let you choose between 3000K or 4000K color temperatures, as well as two different light level – offering four combinations in a single fixture. It comes preset to 3000K and the highest light level but can easily be adjusted to suit your lighting needs. This phase-cut dimmable pole can be mounted directly on the ground or cast in with an anchor bracket (sold separately), and a mounting plate compatible with the Ørsta foundation is available as an accessory. Light distribution Direct Light technic LED 13W 4000K Ra>80 SDCM 3 L80/B20 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP65 IK06 Materials and finish Housing: Aluminium Colour: Grey Optic: Glass Mounting/Connection Pole, wall, bollard or earthing rod, Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 23, B16: 36, C10: 37, C16: 60

Light output 1



1 x LED			
Nominal lamp power	13 W	LOR	100%
Lamp flux	1140 lm	ULOR	21%
Luminous efficacy	88 lm/W	Total flux	1140 lm
CCT	4000 K	Total power	13 W
CRI	80		

Mounting mode

Standing / Bollard, Pole top mounted, Pole integrated

Shape and measurements

Length: 17.32 in
Width: 9.45 in
Height: 90.75 in

Adjustability

Fixed

Electric

System power: 13 W
Appliance Class: II

Protection

IP: 65
IK: 06