


# Product data sheet

URBINO TWILIGHT LED 27W 3300LM 4000K IP66 O5 - FOR RESIDENTIAL AREA ROADS GRAY II  
130222.5L012.041.986  
LUG



Professional streetlight luminaire for LED light sources. Luminaire with twilight sensor. High efficacy to 131 lm/W Mounting: on pillar  $\varnothing 60/76\text{mm}$ , on outriggers  $\varnothing 60/76\text{mm}$  Body: high pressure die-cast aluminum Lateral Surface Wind Exposed:  $0.054\text{ m}^2$  Power supply efficiency  $>95\%$  Power: 220-240V 50/60Hz Lifetime (L90B10): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, knife switch, 10kV surge protection, NTC, access to the driver chamber without the use of tools. Additional information: tilt adjustment:  $-15^\circ$  to  $+15^\circ$  (every  $5^\circ$ ). Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenade, cycle paths. Type of optics: O5 - for residential area roads

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	27 W	CRI	70
Total flux	3300 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	27 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 21.65 in

Width: 9.84 in

Height: 7.68 in

## Adjustability

Tiltable

## Design

Color of housing: Silver gray

## Electric

System power: 27 W

Appliance Class: II

## Integrated sensors

Integrated sensors: Daylight sensor

## Protection

IP: 66

IK: 08