Product data sheet

NEOS - DS
7247-E-3-666-XX
UNILAMP

IP 66 IK 08

NEOS NEOS is a small sized high performing area light. Outstanding optical efficacy, high ambient temperature rating and a wide range of mounting accessory makes NEOS a highly competitive product. The smooth curved design eliminates accumulation of water and dust. The unobtrusive slim design is a great match for commercial and residential lighting tasks. The area light can be either equipped with a photocell, DALI-2 control or basic on-off control gear. NEOS can be equipped with mounting accessories for pole integrated mounting, pole bracket, wall and wall corner. The pole bracket is suitable for Pole diameters up to 105mm. Features: • Photocell for simple and cost effective light management • Easy spec: one luminaire part code multiple mounting options • Supreme surge protection: mains and dimming line 10kV protected • Prewired cable 2000mm

Light output 1



1 x LED

Nominal lamp power	32 W	LOR	88%
Lamp flux	5760 lm	Total flux	5058 lm
Luminous efficacy	180 lm/W	Total power	34 W
CCT	3000 K		
CRI	80		

Light output 2



1 x LED

Nominal lamp power	32 W	LOR	88%
Lamp flux	5760 lm	Total flux	5058 lm
Luminous efficacy	180 lm/W	Total power	34 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 9.27 in
Width: 4.13 in
Height: 9.29 in

Electric

System power: 68 W
Appliance Class: I

Protection

IP: 66
IK: 08

Adjustability

Rotatable, Tiltable