


# Product data sheet

CELINE-2 PNL 625 DDP OP 4000 840 IP20 DALI-2 SET  
EQ10132513  
ESYLUX



LED light with opal cover (diffuser) User interface: DALI-Bus Control system: DALI-2 Installation type: Insert Installation position: Ceiling  
Dimensions: Length 620 mm x Width 620 mm x Height/Depth 65 mm Weight: 3646 g Protection type: IP20 ApplianceClass: Class II  
Permissible ambient temperature: 0 °C...+40 °C Colour: white, similar to RAL 9016 Nominal voltage: 200 - 240 V AC/DC / 50 - 60 Hz  
TotalSystemPower: 33 W Luminous flux: 4200 lm Luminous efficacy: 127 lm/W Colour temperature: 4000 K Colour rendering index  
R<sub>a</sub>: > 80 Rated lifetime L<sub>B</sub>50 at 25 °C: 70000 h<p>ArticleNumber: EQ10132513  
<https://www.esylux.com/p/EQ10132513>

## Light output 1



|                    |          |             |         |
|--------------------|----------|-------------|---------|
| 1 x LED            |          |             |         |
| Nominal lamp power | 33 W     | LOR         | 100%    |
| Lamp flux          | 4000 lm  | Total flux  | 4000 lm |
| Luminous efficacy  | 121 lm/W | Total power | 33 W    |
| CCT                | 4000 K   |             |         |
| CRI                | 81       |             |         |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 24.41 in  
Width: 24.41 in  
Height: 2.56 in

## Adjustability

Fixed

## Design

Color of housing: White

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 33 W  
Controller: DALI  
Appliance Class: II

## Protection

IP: 20  
IK: 02  
Designation labels: CE

## Other operating numbers

Ambient temperature range: 32...104°F