



# Product data sheet

PURE 1 SPOT TRACK  
09.1004/QT-12/20W/35W/50W/22°  
FLOS




Luminaire for three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.

## Light output 1




### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gy6.35
Lamp flux	600 lm	LOR	56%
Luminous efficacy	10 lm/W	Total flux	338 lm
CCT	3000 K	Total power	35 W
CRI	99		



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	20 W	Socket	E27
Lamp flux	300 lm	LOR	56%
Luminous efficacy	8 lm/W	Total flux	169 lm
CCT	2756 K	Total power	22 W
CRI	99		



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gy6.35
Lamp flux	910 lm	LOR	56%
Luminous efficacy	10 lm/W	Total flux	512 lm
CCT	3000 K	Total power	50 W
CRI	99		

## Mounting mode

Ceiling mounted

## Electric

System power: 22-50 W  
Appliance Class: I

#### Shape and measurements

Length: 1.69 in

Width: 4.34 in

Height: 5.31 in

#### Adjustability

Free

#### Protection

IP: 20