


# Product data sheet

PENDANT LUMINAIRE SOLO SLIM OFFICE L1 21W CRI > 80 3000K SI  
 1021.7061 - SOLO SO PEN530-985 LED3100-830 DID SR DALI  
 REGENT



Pendant luminaire Solo Slim Office with LED, system power: 21 W, standby power 0.5 W, luminous flux of luminaire 3100 lm, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 11 A, direct-indirect light emission, ( 61%/39% ), frame in aluminium, silver, neat shadow gap, diffuser in polymethyl methacrylate (PMMA) office-suitable microprismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, 1 integral control gear, DALI, ENEC certified, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0318), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP40, glow wire test 650 °C, impact strength: IK 06, this product contains a light source of energy efficiency class D and EPREL registration number: 1140600 Ø = 530 mm, H = 70 mm, p = 985 mm

## Light output 1



<b>1 x LED</b>			
Nominal lamp power	25 W	LOR	100%
Lamp flux	3100 lm	ULOR	40%
Luminous efficacy	124 lm/W	Total flux	3100 lm
CCT	3000 K	Total power	21 W
CRI	80		

## Mounting mode

Pendant

## Shape and measurements

Length: 20.87 in

Width: 20.87 in

Height: 2.91 in

## Adjustability

Fixed

## Electric

System power: 21 W

Appliance Class: I

## Protection

IP: 40

IK: 06