


Product data sheet

RESCLITE C SPOT AD E1D IP65 WH
42180450
ZUMTOBEL



LED Safety luminaire for illuminating fire-fighting and first-aid equipment and danger spots with minimum output 5 lx; surface mounted; Luminaire with local battery supply for 1 hr. emergency lighting in maintained or non-maintained mode, with automatic test (auto-test) via the luminaire, optional central monitoring via DALI, display of luminaire status via status LED; room height 2.2 to 7 m; high power LED, cool white; optimum thermal management via heat sink; lens made of polycarbonate (PC); luminaire housing made of die-cast aluminium in powder coated white finish, RAL 9016; white cover made of fibre-glass reinforced PC with transparent PC light outlet; cover is screw-fitted; through-wiring plug-in terminals for wire cross-sections up to 2.5 mm²; side cable-entry possible; luminaire total power: 4 W; power supply: 230V AC; rotary switch for mechanical address-setting; degree of protection: IP65, class of protection: SC1; Impact strength: IK04; non-maintained and maintained mode possible, Maintained mode: +5°C to +30°C, Non-maintained mode: +5°C to +35°C; Dimensions: 200 x 130 x 57 mm; weight: 1.05 kg; Luminaire wired with halogen-free leads

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4 W	CRI	99
Total flux	141 lm	LOR	100%
Luminous efficacy	35 lm/W	Total power	4 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 7.87 in
Width: 5.12 in
Height: 2.24 in
Weight: 1.1 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 4 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 65
IK: 04
Designation labels: CE, ENEC